


ST 380



CARACTERISTIQUES MECANIQUES PHYSICAL SPECIFICATIONS

TENSION NOMINALE / <i>NOMINAL VOLTAGE</i>		12 V
CAPACITE / <i>NOMINAL CAPACITY (20HR)</i>		40 Ah
DIMENSIONS	Longueur / <i>Length</i>	197 mm
	Largeur / <i>Width</i>	165 mm
	Hauteur / <i>Total Height (with terminal)</i>	170 mm
MASSE / <i>WEIGHT</i>		13.8 Kg
TYPE DE BORNE / <i>STANDARD TERMINAL</i>		Insert femelle M6 / <i>Female insert M6</i>
COUPLE DE SERRAGE / <i>CLAMPING TORQUE</i>		8 Nm

CARACTERISTIQUES ELECTRIQUES ELECTRICAL SPECIFICATIONS

CAPACITE / <i>RATED CAPACITY</i> <i>1,8 V/élément - 1,8 V/cell</i>	20 hour rate	40 AH
	10 hour rate	38 AH
	5 hour rate	31.9 AH
	3 hour rate	28.1 AH
	1 hour rate	21.4 AH
INFLUENCE DE LA TEMPERATURE SUR LA CAPACITE / <i>CAPACITY</i> <i>AFFECTED BY TEMPERATURE</i>	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
RESISTANCE INTERNE / <i>INTERNAL RESISTANCE</i>	Fully charged battery 10 milliohms (25°C, 77°F)	
COURANT MAXI EN 10 sec. / <i>CURRENT MAXI 10S</i>		0.380 KA (end of voltage 1,6V/cell)
COURANT MAXI EN 5 sec. / <i>CURRENT MAXI 5S</i>		0.570 KA (end of voltage 1,6V/cell)
COURANT DE COURT-CIRCUIT / <i>SHORT-CIRCUIT CURRENT</i>		0.950 KA